



## Artikelnummer / Article number: 464FUB+1

Absperr-Stilpfosten Serie 464B Ø 60 mm, umlegbar, für Dübelbefestigung selbsteinrastende Verriegelung mit Bodenplatte 100 x 150 mm, mit Dreikantverschluss nach DIN 3223, mit 1 Öse

### Artikeltext

Absperr-Stilpfosten Serie 464B Ø 60 mm

Absperr-Stilpfosten mit Ziernut aus Stahlrundrohr Ø 60 mm, ca. 950 mm Überflur, feuerverzinkt und anthrazitgrau DB 703 beschichtet.

- umlegbar, für Dübelbefestigung selbsteinrastende Verriegelung mit Bodenplatte 100 x 150 mm
- mit Dreikantverschluss nach DIN 3223
- mit 1 Öse

### Verwendungszweck

Der Verwendungszweck eines Absperr-Stilpfostens liegt in der eleganten und zugleich effektiven Abgrenzung sowie Lenkung von Personenbereichen im Innen- und Außenbereich. Er wird vor allem dort eingesetzt, wo neben Funktionalität auch ein ansprechendes Erscheinungsbild gefragt ist. In Kombination mit Kordeln oder Gurten ermöglicht der Absperr-Stilpfosten eine klare Wegeführung und Zugangskontrolle. Ob in Hotels, bei Veranstaltungen, in Eingangsbereichen oder öffentlichen Einrichtungen: Der Absperr-Stilpfosten ist eine stilvolle Lösung für Ordnung, Sicherheit und repräsentative Bereiche.

### Technische Daten

Gewicht: 7 kg  
Abmessungen: 60 mm x 1400 mm x 60 mm  
Material:  
S235 JR

Oberfläche:  
Feuerverzinkt und Pulverbeschichtet

EAN / EAN number: 4250384771584  
Frachtkategorie / Freight category: A

Ornamental bollard Series 464B Ø 60 mm, foldable, self-engaging lock to be fixed by plugs, with base plate 100 x 150 mm, with triangular locking mechanism acc. with DIN 3223, with 1 eyelet

### Item description

Ornamental bollard Series 464B Ø 60 mm

The ornamental bollard series Ø 60 mm  
A light-weight but very stylish version of our ornamental bollards. Barrier ornamental bollard of round steel tube Ø 60 mm, approx. 950 mm above ground, hot-dip galvanized and coated anthracite grey (RAL 7016).

- foldable, self-engaging lock to be fixed by plugs, with base plate 100 x 150 mm
- with triangular locking mechanism acc. with DIN 3223
- with 1 eyelet

### Technical specifications

Weight: 7 kg  
Dimensions: 60 mm x 1400 mm x 60 mm  
material:  
S235 JR

surface:  
hot dipped galvanized and powder coated

\* Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

\* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.