



Número de artículo / Article number: 20215

EAN / EAN number: 4250384701680
Categoría de carga / Freight category: A

"Tirante de canal "perfecto Ø32 mm, Talla 4 1,40 m - 1,70 m
31,70 kN - 26,50 kN

Trench shoring "Perfect" Ø 32 mm, Size 4: 1.40 m - 1.70 m
31.70 kN - 26.50 kN



Descripción

"Tirante de canal "perfecto Ø32 mm

"Tirante de canal "perfecto

Para uso en ingeniería civil, para arriostrar y soportar paredes de conductos.

- Husillo: Ø32 mm
- Según DIN 4124 con marca de ensayo TBG-4P 32
- Tubo exterior: Ø42,4 mm
- Con placas de garras de 70 mm x 70 mm en ambos lados
- Acabado: pintado marrón

- Talla 4 1,40 m - 1,70 m 31,70 kN - 26,50 kN

Item description

Trench shoring "Perfect" Ø 32 mm

Trench shoring "Perfect" Ø 32 mm for civil engineering use, for bracing and supporting canal walls, acc. to DIN 4124 with test label TBG-4P 32, spindle: Ø 32 mm, outer tube: Ø 42.4 mm with claw plates 70 mm x 70 mm on both sides, spindle and tube are firmly connected with each other by a locking ring.

- Size 4: 1.40 m - 1.70 m 31.70 kN - 26.50 kN

Datos técnicos

Peso: 8 kg
Dimensiones: 70 mm x 1400 mm x 70 mm
material:
S235 JR

surface:
painted in RAL 8017

Technical specifications

Weight: 8 kg
Dimensions: 70 mm x 1400 mm x 70 mm
material:
S235 JR

surface:
painted in RAL 8017

* Todas las especificaciones son valores aproximados (en algunos casos con el redondeo estándar de la industria para una mejor comprensión) y están destinadas únicamente a la comprensión del producto, pero no como base para la construcción de accesorios, bastidores de almacenamiento, adaptaciones, productos combinados o similares. Toda la información se facilita sin garantía, por lo que no asumimos responsabilidad alguna por posibles errores y sus consecuencias.

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.