# Datasheet / Datenblatt

Article number / Artikelnummer: VPSE5L

EAN number / EAN: 4250384789428
Freight category / Frachtkategorie: S

V-Gate-Simple

V-Gate-Simple

## Item description

V-Gate-Simple

V-Gate-Simple
Simple, Efficient, Reliable—simplifying the world of mobile sliding gates.

The V-Gate-Simple—the smart solution for easy access control at construction sites and events. With its clean and simple design, this sliding gate is the perfect choice for you if you value user-friendliness and efficiency. The V-Gate-Simple is set up once and can then be conveniently controlled via a wireless remote. Thanks to its versatility, you can use it as a mobile or stationary unit and move it effortlessly. Despite its compact size, the V-Gate-Simple offers a generous opening width ranging from 3.6 m to 5.5 m to ensure a smooth flow of traffic. Equipped with practical features such as a printable aluminum composite panel, a CEE plug, a rack-and-pinion drive, an LED flashing light, and a photoelectric sensor, it meets all the requirements for modern access control. Experience the perfect combination of simplicity, performance, and reliability for your access control needs with the V-Gate-Simple.

· Shipping dimensions: 2.00 x 5.74 x 2.36 m (2.00 x 7.57 x 2.36 m)
· Weight: 1,785 kg (1,898 kg)
· Opening width: 3.6 m (5.5 m)
· Mounted on a mobile concrete platform with leveling feet
· Suitable for outdoor use
· Connection via 230 V CEE plug
· Module 4 rack-and-pinion drive
· Expandable control system
· Photoelectric sensor
· LED rotating beacon
· Force-sensing cut-off
· Flexible folding mechanism
· Supplied with 2 handheld transmitters
· Access control systems can be connected on both sides
· Flexible fence integration
· Custom powder coating
· In very cold regions, built-in heaters with thermostats can help ensure that the electrical system remains operational at all times
· We can equip our gates with either photoelectric sensors or laser scanners—depending on the application’s requirements

## Artikeltext

V-Gate-Simple

V-Gate-Simple
Simpel, Effizient, Zuverlässig - die Welt der mobilen Schiebetore vereinfacht.

Das V-Gate-Simple – die smarte Lösung für deine einfache Zugangskontrolle auf Baustellen und Events. Mit seiner klaren und simplen Konstruktion ist dieses Schiebetor die optimale Wahl für dich, wenn du Wert auf Benutzerfreundlichkeit und Effizienz legst. Das V-Gate-Simple wird einmal aufgestellt und lässt sich anschließend bequem per Funkfernbedienung steuern. Dank seiner Vielseitigkeit kannst du es mobil oder stationär einsetzen und mühelos versetzen. Trotz seiner kompakten Größe bietet das V-Gate-Simple eine großzügige Öffnungsbreite von 3,6 m bis zu 5,5 m, um einen reibungslosen Verkehrsfluss zu gewährleisten. Ausgestattet mit praktischen Features wie einer bedruckbaren Aluverbundplatte, einem CEE-Stecker, einem Zahnstangenantrieb, einem LED-Blinklicht und einer Lichtschranke erfüllt es alle Anforderungen an eine moderne Zugangskontrolle. Erlebe mit dem V-Gate-Simple die perfekte Kombination aus Einfachheit, Leistung und Zuverlässigkeit für deine Zugangskontrollanforderungen.

· Transportmaß: 2,00 x 5,74 x 2,36 m (2,00 x 7,57 x 2,36 m)
· Gewicht: 1785 kg (1898 kg)
· Öffnungsweite: 3,6 m (5,5 m)
· Auf mobiler Betonplattform mit Stellfüßen
· Für den Außenbetrieb geeignet
· Anschluss per 230 V CEE-Stecker
· Modul 4 Zahnstangenantrieb
· Erweiterbare Steuerung
· Lichtschranke
· LED-Rundumleuchte
· Kraftabschaltung
· flexibler Faltmechanismus
· Auslieferung mit 2x Handsendern
· Beidseitige Anbindung von Zutrittskontrollen möglich
· Flexible Zaunanbindung
· Individuelle Pulverbeschichtung
· In sehr kalten Regionen können verbaute Heizungen mit Thermostaten dazu beitragen, dass die Elektrik stets einsatzbereit bleibt
· Unsere Tore können wir sowohl mit Lichtschranken als auch mit Laserscannern versehen – je nachdem, was die Anwendung erfordert

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.
* Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen leidglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.
* Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen leidglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.