



Artikelnummer / Article number: 480FUHB+2

Afsluitpalen Serie 480B Ø 82 mm, Omkeerbaar, zelfsluitend vergrendelingsmechanisme voor plaatsing in beton, met thermisch verzinkte grondkoker type 47, met driehoeksslot volgens DIN 3223, met 2 oogjes

Omschrijving

Afsluitpalen Serie 480B Ø 82 mm

Stijl paal
gemaakt van stalen buis Ø 82 mm
ca. 800 mm boven de grond, thermisch verzinkt en
antracietgrijs (RAL 7016) gecoat
met halve bol

- Omkeerbaar, zelfsluitend vergrendelingsmechanisme voor plaatsing in beton, met thermisch verzinkte grondkoker type 47
- met driehoeksslot volgens DIN 3223
- met 2 oogjes

Technische gegevens

Gewicht: 12,5 kg
Afmetingen: 82 mm x 1200 mm x 82 mm
materiaal:
S235 JR

surface:
hot dipped galvanized and powder coated

* Alle specificaties zijn waarden bij benadering (in sommige gevallen met afrondingen volgens de industriestandaard voor een beter begrip) en zijn uitsluitend bedoeld om het product te begrijpen, maar niet als basis voor de constructie van accessoires, opbergrekken, aanpassingen, combinatieproducten of soortgelijke producten. Wij aanvaarden geen aansprakelijkheid voor eventuele fouten en de daaruit voortvloeiende gevolgen.

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.

EAN / EAN number: 4250384745363
Vrachtcategorie / Freight category: A

Ornamental bollard Series 480B Ø 82 mm, foldable, self-engaging lockfor casting in concrete, with hot-dip galvanized ground socket part-no. 470.60approx. 400 mm below ground, with triangular locking mechanism acc. with DIN 3223, with 2 eyelets

Item description

Ornamental bollard Series 480B Ø 82 mm

Ornamental bollard
of steel tube Ø 82 mm
approx. 800 mm above ground, hot-dip galvanized
and coated anthracite grey (RAL 7016)

- foldable, self-engaging lockfor casting in concrete, with hot-dip galvanized ground socket part-no. 470.60approx. 400 mm below ground
- with triangular locking mechanism acc. with DIN 3223
- with 2 eyelets

Technical specifications

Weight: 12,5 kg
Dimensions: 82 mm x 1200 mm x 82 mm
material:
S235 JR

surface:
hot dipped galvanized and powder coated