Fiche technique / Datasheet


Numéro d'article / Article number: 415_60VPB

Numéro EAN / EAN number: 4250384707408
Catégorie de fret / Freight category: D

Barrière manuelle avec ressort à pression de gaz et poteau d'appui fixe, largeur libre: 6000 mm, pour cadenas

Manual barrier with pneumatic spring and fixed pole support, clear width: 6000 mm, for padlock





Description de l'article

Barrière manuelle avec ressort à pression de gaz et poteau d'appui fixe

Barrière manuelle, avec ressort à pression de gaz et poteau, d'appui fixe, Appui principal: tube rectangulaire, 120 x 80 mm avec platine 360 x 360 x 8 mm à, cheviller, 4 alésages Ø 20 mm incl. pour, l'ancrage, galvanisé à chaud et peint en rouge, par poudrage. Blocage par boulon, la barrière, étant ouverte / fermée, Poreau support: tube d'acier 70 x 70mm avec, platine 220 x 220 x 8 mm, 4 alésages Ø 20 mm, incl. pour l'ancrage, Flèche de barrière: tube d'aluminium à paroi, épaisse Ø 80mm, peint par poudrage, avec, bandes réfléchissantes rouges., Serrure triangulaire et serrure profilée à pistons sur l'appui principal, Largeur totale: Largeur de passage + env. 180 mm, Hauteur: env. 950 mm hors sol

- largeur libre: 6000 mm
- pour cadenas

Item description

Manual barrier with pneumatic spring and fixed pole support

Manual barrier
with pneumatic spring and fixed pole support
Main support: Steel construction 120 x 80 mm square tube with base plate 360 x 360 x 8 mm for plugging down, including 4 holes Ø 20 mm for anchor, hot-dip galvanized and powdercoated red, barrier arm can be fixed in open and closed position
Supporting post: Steel tube 70 x 70 mm with base plate 220 x 220 x 8 mm, including 4 holes Ø 20 mm for anchor
Barrier arm: Thick-walled Ø 80 mm aluminium tube, powder-coated with red reflecting stripes
Locking mechanism at the post support
Total width: Clear width + approx. 180 mm
Height: approx. 950 mm above ground

- clear width: 6000 mm
- for padlock

Données techniques

Poids: 54 kg
Dimensions: 360 mm x 6180 mm x 957 mm
matériau:
S235 JR

surface:
galvanisée a chaud et revêtement par poudre

Technical specifications

Weight: 54 kg
Dimensions: 360 mm x 6180 mm x 957 mm
material:
S235 JR

surface:
hot dipped galvanized and powder coated

* Toutes les données sont des valeurs indicatives (en partie avec les arrondis habituels dans la branche pour une meilleure compréhension) et servent uniquement à la compréhension du produit, mais pas comme base pour la construction d'accessoires, de supports de stockage, d'adaptations, de produits combinés ou autres. Toutes les indications sont fournies sans garantie, nous déclinons toute responsabilité pour d'éventuelles erreurs et les conséquences qui en résultent.
* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.