




## Numéro d'article / Article number: 460BG

Poteau de dissuasion tube d'acier Ø 60 x 2,5 mm jaune / noire, stationnaire, à bétonner avec ancrage, sans anneaux



### Description de l'article

Poteau de dissuasion tube d'acier Ø 60 x 2,5 mm jaune / noire

Poteau de dissuasion, tube d'acier Ø 60 x 2,5 mm, avec capuchon d'acier soudé, 900 mm hors sol, galvanisé à chaud et revêtu en jaune avec trois bandes noires

- stationnaire, à bétonner avec ancrage
- sans anneaux

### Données techniques

Poids: 4,5 kg

Dimensions: 60 mm x 1300 mm x 60 mm

matériau:

S235 JR

surface:

galvanisée à chaud et revêtement par poudre


\* Toutes les données sont des valeurs indicatives (en partie avec les arrondis habituels dans la branche pour une meilleure compréhension) et servent uniquement à la compréhension du produit, mais pas comme base pour la construction d'accessoires, de supports de stockage, d'adaptations, de produits combinés ou autres. Toutes les indications sont fournies sans garantie, nous déclinons toute responsabilité pour d'éventuelles erreurs et les conséquences qui en résultent.

\* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.

Numéro EAN / EAN number: 4250384741662

Catégorie de fret / Freight category: A

Barrier post steel tube Ø 60 x 2,5 mm yellow / black, stationary, for casting in concrete with ground anchor, without eyelet



### Item description

Barrier post steel tube Ø 60 x 2,5 mm yellow / black

Barrier posts

Steel tube Ø 60 x 2.5 mm

with welded steel cap

900 mm above ground

hot-dip galvanized and coated yellow with three black stripes

- stationary, for casting in concrete with ground anchor
- without eyelet

### Technical specifications

Weight: 4,5 kg

Dimensions: 60 mm x 1300 mm x 60 mm

material:

S235 JR

surface:

hot dipped galvanized and powder coated: polyester powder suitable for exterior facades