Datasheet / Datenblatt

Article number / Artikelnummer: VPFOS

EAN number / EAN: 4250384789480
Freight category / Frachtkategorie: S

V-Fold-Steelplate

V-Fold-Steelplate

Item description

V-Fold-Steelplate

V-Fold Steelplate
Speed meets security—the mobile gate solution for efficient access.

When security and speed are equally important, the V-Fold Steelplate stands out as a top-tier electric rapid-fold gate solution. Manufactured from galvanized steel and mounted on a mobile steel plate, it combines stability, mobility, and modern technology in a well-designed system. With its rapid opening and closing motion, the gate ensures smooth operations while reliably protecting sensitive areas from unauthorized access. Ideal for construction sites, logistics areas, or temporary facilities—anywhere efficiency, control, and security must go hand in hand. A flexible access system that demonstrates how function and design come together as one.

· Shipping dimensions: 2.00 x 6.25 x 2.45 m
· Weight: 1,836 kg
· Opening width: 5.5 m
· Opening/closing time: ~6.5 s
· Mounted on a mobile steel plate
· Suitable for outdoor use
· Power connection via 230 V CEE plug
· 24 V motors for heavy-duty operation
· Expandable control system
· Photoelectric sensor
· LED rotating beacon
· Force-sensing shut-off
· Bi-folding mechanism
· Supplied with 2 handheld transmitters
· Access control systems can be integrated on both sides
· Flexible fence integration
· Custom powder coating
· The powerful motors can be adjusted to meet individual requirements via the external control system using numerous parameters
· The bi-folding mechanism ensures that the V-Fold folds up quickly and saves space
· The steel plate is rigidly connected to the two upright posts, enabling quick installation without time-consuming alignment
· In tight spaces, the folding gate has the advantage of requiring no additional space next to the opening area

Artikeltext

V-Fold-Steelplate

V-Fold-Steelplate
Schnelligkeit trifft Sicherheit – die mobile Torlösung für effiziente Zugänge.

Wenn Sicherheit und Geschwindigkeit gleichermaßen gefragt sind, überzeugt das V-Fold-Steelplate als elektrische Schnellfalttor-Lösung auf höchstem Niveau. Gefertigt aus verzinktem Stahl und montiert auf einer mobilen Stahlplatte, vereint es Stabilität, Mobilität und moderne Technologie in einem durchdachten System. Mit seiner schnellen Öffnungs- und Schließbewegung ermöglicht das Tor einen reibungslosen Ablauf und schützt gleichzeitig sensible Bereiche zuverlässig vor unbefugtem Zutritt. Ideal für Baustellen, Logistikflächen oder temporäre Anlagen – überall dort, wo Effizienz, Kontrolle und Sicherheit Hand in Hand gehen sollen. Ein flexibles Zugangssystem, das zeigt, wie Funktion und Design zu einer Einheit werden.

· Transportmaß: 2,00 x 6,25 x 2,45 m
· Gewicht: 1836 kg
· Öffnungsweite: 5,5 m
· Öffnungs-Schließzeit ~6,5 s
· Auf mobiler Stahlplatte
· Für den Außenbetrieb geeignet
· Anschluss per 230 V CEE-Stecker
· 24 V Motoren für Intensivbetrieb
· Erweiterbare Steuerung
· Lichtschranke
· LED-Rundumleuchte
· Kraftabschaltung
· Bi-Folding Mechanismus
· Auslieferung mit 2x Handsendern
· Beidseitige Anbindung von Zutrittskontrollen möglich
· Flexible Zaunanbindung
· Individuelle Pulverbeschichtung
· Die kraftvollen Motoren können über die externe Steuerung in zahlreichen Parametern an individuelle Anforderungen angepasst werden
· Der Bi-Folding-Mechanismus sorgt dafür, dass das V-Fold schnell und platzsparend zusammenklappt
· Die Stahlplatte ist starr mit den beiden Standpfosten verbunden und ermöglicht einen schnellen Aufbau ohne aufwendige Ausrichtung
· bei engen Platzverhältnissen hat das Falttor den Vorteil, dass kein zusätzlicher Platz neben dem Öffnungsbereich erforderlich ist

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.
* Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen leidglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.
* Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen leidglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.