



Artikelnummer / Article number: 490FB+1

Alu-Stilpfosten Serie 490B, herausnehmbar, selbsteinrastende Verriegelung mit feuerverzinkter Bodenhülse Typ 460.40, ca. 400 mm Unterflur, mit Dreikantverschluss nach DIN 3223, mit 1 Öse

Artikeltext

Alu-Stilpfosten Serie 490B

Alu-Stilpfosten
Aluminiumguss mit Stahlrohrkern,
ca. 900 mm Überflur, mattschwarz
beschichtet

- herausnehmbar, selbsteinrastende Verriegelung mit feuerverzinkter Bodenhülse Typ 460.40, ca. 400 mm Unterflur, mit Dreikantverschluss nach DIN 3223
- mit 1 Öse

Technische Daten

Gewicht: 9,5 kg
Abmessungen: 110 mm x 1300 mm x 110 mm
Material:
Aluminium

Oberfläche:
Feuerverzinkt und Pulverbeschichtet

* Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen lediglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.

EAN / EAN number: 4250384729080
Frachtkategorie / Freight category: A

Aluminium ornamental bollard series 490, removable, with triangular locking mechanism. with DIN 3223, self-engaging lock with hot-dip galvanized ground socket part-no. 460.40 approx. 400 mm below ground, with 1 eyelet

Item description

Aluminium ornamental bollard series 490

Aluminium ornamental post
Cast aluminium with steel rod core, approx. 900 mm above ground, coated matt black

- removable, with triangular locking mechanism. with DIN 3223, self-engaging lock with hot-dip galvanized ground socket part-no. 460.40 approx. 400 mm below ground
- with 1 eyelet

Technical specifications

Weight: 9,5 kg
Dimensions: 110 mm x 1300 mm x 110 mm
material:
aluminium

surface:
hot dipped galvanized and powder coated