



Número de artículo / Article number: 411_40FPB

EAN / EAN number: 4250384705992
Categoría de carga / Freight category: D

Barrera con contrapeso y soporte, Anchura libre: 4000 mm, con cierre triangular

Access barrier with counterweight and supporting post, clear width: 4000 mm, with triangular lock



Descripción

Barrera con contrapeso y soporte

Barrera de paso

Soporte principal: estructura de acero de tubo cuadrado de 70 x 70 mm con placa de base de 360 x 360 x 8 mm, para fijación con tacos, incluye 4 orificios de Ø 20 mm para anclajes, galvanizado en caliente y con recubrimiento en polvo rojo

Poste de apoyo: tubo de acero de 70 x 70 mm con placa de base de 220 x 220 x 8 mm, incl. 4 orificios de Ø 20 mm para anclajes

Barra de la barrera: tubo de aluminio de pared gruesa de Ø 80 mm con contrapeso de hormigón, con recubrimiento en polvo blanco y franjas reflectantes rojas

Cierre: bloqueo en el soporte de apoyo cuando la barrera está abierta mediante un perno de inserción en el soporte principal

Ancho total: ancho interior + aprox. 900 mm

Altura: aprox. 950 mm sobre el suelo

- Anchura libre: 4000 mm
- con cierre triangular

Datos técnicos

Peso: 70 kg

Dimensiones: 360 mm x 4900 mm x 360 mm

material:

S235 JR

surface:

hot dipped galvanized and powder coated

Item description

Access barrier with counterweight and supporting post

Access barrier

Main post: Steel structure made of 70 x 70 mm square tubing with a base plate measuring 360 x 360 x 8 mm, for dowel mounting, including 4 holes (Ø 20 mm) for anchors, hot-dip galvanized and red powder-coated

Support post: 70 x 70 mm steel tube with 220 x 220 x 8 mm base plate, incl. 4 Ø 20 mm holes for anchors

Barrier arm: thick-walled Ø 80 mm aluminum tube with concrete counterweight, white powder-coated with red reflective stripes

Locking mechanism: Locking mechanism on the support post when the barrier is open, using a pin on the main support

Overall width: Clear width + approx. 900 mm

Height: Approx. 950 mm above ground

- clear width: 4000 mm
- with triangular lock

Technical specifications

Weight: 70 kg

Dimensions: 360 mm x 4900 mm x 360 mm

material:

S235 JR

surface:

hot dipped galvanized and powder coated

* Todas las especificaciones son valores aproximados (en algunos casos con el redondeo estándar de la industria para una mejor comprensión) y están destinadas únicamente a la comprensión del producto, pero no como base para la construcción de accesorios, bastidores de almacenamiento, adaptaciones, productos combinados o similares. Toda la información se facilita sin garantía, por lo que no asumimos responsabilidad alguna por posibles errores y sus consecuencias.

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.