Datasheet / Datenblatt

Article number / Artikelnummer: 467_13

EAN number / EAN: 4250384711146
Freight category / Frachtkategorie: B

Safety railing / border railings, Fixed post for top and quarter-bent barfor casting in concrete, Corner post for top and quarter-bent bar, hot-dip galvanized

Schutzgeländer / Rabattengeländer, Standpfosten für Ober- und Knieholm zum Einbetonieren, Eckpfosten für Ober- und Knieholm, feuerverzinkt



Item description

Safety railing / border railings

Safety railings
Are assembled from prefabricated parts on site. Hinge joints make the railings very flexible. The hinge joints can be positioned vertically and horizontally to 90°.
Fixed post for top bar
Steel tube Ø 60 mm, with aluminium ball head
total length approx. 1500 mm

- Fixed post for top and quarter-bent barfor casting in concrete
- Corner post for top and quarter-bent bar
- hot-dip galvanized

Artikeltext

Schutzgeländer / Rabattengeländer

Schutzgeländer
Standpfosten für Oberholm
Stahlrohr Ø 60 mm, mit Alukugelkopf
Gesamtlänge ca. 1500 mm

- Standpfosten für Ober- und Knieholm zum Einbetonieren
- Eckpfosten für Ober- und Knieholm
- feuerverzinkt

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.
* Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen leidglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.

Verwendungszweck

Der Verwendungszweck eines Schutzgeländers liegt in der zuverlässigen Sicherung von Arbeitsbereichen, Verkehrswegen und Gefahrenstellen gegen Absturz oder unbefugtes Betreten. Es wird eingesetzt, um Personen vor Risiken an Kanten, Öffnungen, Treppen, Plattformen oder Baustellen zu schützen und gleichzeitig eine klare Abgrenzung zu schaffen. Durch seine stabile Konstruktion sorgt das Schutzgeländer für hohe Sicherheit und Orientierung im Arbeitsumfeld. Ob im Bauwesen, in der Industrie oder im öffentlichen Raum: Das Schutzgeländer ist eine unverzichtbare Lösung für Arbeitsschutz, Sicherheit und strukturierte Bereiche.

Technical specifications

Weight: 5 kg
Dimensions: 60 mm x 1500 mm x 60 mm
material:
S235 JR

surface:
hot dipped galvanized acc. to DIN ISO 1461

Technische Daten

Gewicht: 5 kg
Abmessungen: 60 mm x 1500 mm x 60 mm
Material:
S235 JR

Oberfläche:
Feuerverzinkung nach DIN ISO 1461

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.
* Alle Angaben sind Richtwerte (teilweise mit branchenüblichen Rundungen zum besseren Verständnis) und dienen leidglich zum Produktverständnis, nicht aber als Basis zum Bau von Zubehörteilen, Lagergestellen, Adaptierungen, Kombinationsprodukten oä. Alle Angaben sind ohne Gewähr, für evtl. Fehler und resultierende Folgen übernehmen wir keine Verantwortung.