



Artikelnummer / Article number: 484FUHB+1

Afsluitpalen Serie 484B Ø 82 mm, omkeerbaar, zelfsluitend vergrendelingsmechanisme Voor plaatsing in beton, met thermisch verzinkte grondkoker type 470.60 ca. 400 mm onder maaiveld, met driehoeksslot volgens DIN 3223, met 1 oogje

Omschrijving

Afsluitpalen Serie 484B Ø 82 mm

Stijl meerpaal
gemaakt van ronde stalen buis Ø 82 mm
ca. 900 mm boven de grond, thermisch verzinkt
en gecoat, kleur: RAL 9005 mat (matzwart)
met kogelkop

- omkeerbaar, zelfsluitend vergrendelingsmechanisme Voor plaatsing in beton, met thermisch verzinkte grondkoker type 470.60 ca. 400 mm onder maaiveld
- met driehoeksslot volgens DIN 3223
- met 1 oogje

Technische gegevens

Gewicht: 13 kg
Afmetingen: 82 mm x 1300 mm x 82 mm
materiaal:
S235 JR

surface:
hot dipped galvanized and powder coated

* Alle specificaties zijn waarden bij benadering (in sommige gevallen met afrondingen volgens de industriernorm voor een beter begrip) en zijn uitsluitend bedoeld om het product te begrijpen, maar niet als basis voor de constructie van accessoires, opbergrekken, aanpassingen, combinatieproducten of soortgelijke producten. Wij aanvaarden geen aansprakelijkheid voor eventuele fouten en de daaruit voortvloeiende gevolgen.

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.

EAN / EAN number: 4250384745493
Vrachtcategorie / Freight category: A

Ornamental bollard Series 484B Ø 82 mm, foldable, self-engaging lockfor casting in concrete, with hot-dip galvanized groundsocket part-no. 470.60, approx. 400 mm below ground, with triangular locking mechanism acc. with DIN 3223, with 1 eyelet

Item description

Ornamental bollard Series 484B Ø 82 mm

Ornamental bollard
of round steel tube Ø 82 mm
approx. 900 mm above ground, hot-dip galvanized and coated, color: RAL 9005 matt (jet black)

- foldable, self-engaging lockfor casting in concrete, with hot-dip galvanized groundsocket part-no. 470.60, approx. 400 mm below ground
- with triangular locking mechanism acc. with DIN 3223
- with 1 eyelet

Technical specifications

Weight: 13 kg
Dimensions: 82 mm x 1300 mm x 82 mm
material:
S235 JR

surface:
hot dipped galvanized and powder coated