



Número de artículo / Article number: 50002-24

Eslingas redondas con doble funda Capacidad de carga 2000 kg, Anchura de la cinta: 37,00 mm, Longitud de circulación: 4,00 m; longitud efectiva: 2,0 m

Descripción

Eslingas redondas con doble funda Capacidad de carga 2000 kg

Eslingas redondas

Para la elevación segura de mercancías.

- con doble funda capacidad de carga 2000 kg
- de tejido resistente -según DIN 60005
- Factor de seguridad: 7:1
- Material: 100 % poliéster
- maneable, ligero e insensible al calor, frío o humedad
- Gama de aplicación -40°C a +100°C

- Anchura de la cinta: 37,00 mm
- Longitud de circulación: 4,00 m; longitud efectiva: 2,0 m

Datos técnicos

Peso: 0,88 kg
Dimensiones: 70 mm x 260 mm x 50 mm
material:
polyester

* Todas las especificaciones son valores aproximados (en algunos casos con el redondeo estándar de la industria para una mejor comprensión) y están destinadas únicamente a la comprensión del producto, pero no como base para la construcción de accesorios, bastidores de almacenamiento, adaptaciones, productos combinados o similares. Toda la información se facilita sin garantía, por lo que no asumimos responsabilidad alguna por posibles errores y sus consecuencias.

* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.

EAN / EAN number: 4250384727666

Categoría de carga / Freight category: A

Endless sling with double sheath carrying power 2000 kg, Strap width: 37.00 mm, Full length 4.0 m Useful length 2.0 m

Item description

Endless sling with double sheath carrying power 2000 kg

Endless sling with double sheath carrying power 2000 kg made of heavy-duty fabric – acc. to DIN 60005 safety factor: 7:1, material 100 % polyester, easy to handle, light-weight and insensitive to heat, cold and moisture;
temperature range: -40°C to +100°C. For safe lifting of loads

- Strap width: 37.00 mm
- Full length 4.0 m Useful length 2.0 m

Technical specifications

Weight: 0,88 kg
Dimensions: 70 mm x 260 mm x 50 mm
material:
polyester