



## Artikelnummer / Article number: 477UZHB+2

Afsluitpalen Serie 477B Ø 76 mm, Omkeerbaar, zelfsluitend vergrendelingsmechanisme voor plaatsing in beton, met thermisch verzinkte grondkoker type 47, Met profielcilinderslot en drie sleutels, met 2 oogjes

## Omschrijving

Afsluitpalen Serie 477B Ø 76 mm

Afzetpaal  
gemaakt van stalen buis Ø 76 mm  
ca. 950 mm boven de grond, thermisch verzinkt en antracietgrijs (RAL 7016) antracietgrijs gecoat met decoratieve kap

- Omkeerbaar, zelfsluitend vergrendelingsmechanisme voor plaatsing in beton, met thermisch verzinkte grondkoker type 47
- Met profielcilinderslot en drie sleutels
- met 2 oogjes

## Technische gegevens

Gewicht: 10,5 kg  
Afmetingen: 76 mm x 1350 mm x 76 mm  
material:  
S235 JR

surface:  
hot dipped galvanized and powder coated

\* Alle specificaties zijn waarden bij benadering (in sommige gevallen met afrondingen volgens de industriernorm voor een beter begrip) en zijn uitsluitend bedoeld om het product te begrijpen, maar niet als basis voor de constructie van accessoires, opbergrekken, aanpassingen, combinatieproducten of soortgelijke producten. Wij aanvaarden geen aansprakelijkheid voor eventuele fouten en de daaruit voortvloeiende gevolgen.

\* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.

EAN / EAN number: 4250384745301  
Vrachtcategorie / Freight category: A

Ornamental bollard Series 477B Ø 76 mm, foldable, self-engaging lockfor casting in concrete, with hot-dip galvanized ground socket part-no. 470.60approx. 400 mm below ground, with Euro profile cylinder lock and three keys, with 2 eyelets

## Item description

Ornamental bollard Series 477B Ø 76 mm

Ornamental bollard  
of steel tube Ø 76 mm  
approx. 950 mm above ground, hot dip galvanized and coated anthracite-grey (RAL 7016)

- foldable, self-engaging lockfor casting in concrete, with hot-dip galvanized ground socket part-no. 470.60approx. 400 mm below ground
- with Euro profile cylinder lock and three keys
- with 2 eyelets

## Technical specifications

Weight: 10,5 kg  
Dimensions: 76 mm x 1350 mm x 76 mm  
material:  
S235 JR

surface:  
hot dipped galvanized and powder coated