




Artikelnummer / Article number: 421\_94

EAN / EAN number: 4250384747435  
Vrachtcategorie / Freight category: A

Scooter rij parker, Voor deuveles

Scooter - serial parking, To be fixed by plugs



## Omschrijving

Scooter rij parker

Scooter - rij parker

Om scooters of e-scooters netjes en veilig te parkeren.

- Met afsluitbare borgringen voor hangslot als diefstalbeveiliging
- de afsluitbare ringen kunnen naar wens open en dicht worden getrokken; een hangslot kan door de parallelle gaten op de twee platen worden bevestigd om het apparaat te beveiligen
- vierkante dwarsbalk van stalen buis 40 x 40 mm
- Totale breedte 1500 mm voor 5 parkeerplaatsen
- Hoogte ca. 650 mm boven maaiveld

Thermisch verzinkt

- Voor deuveles

## Technische gegevens

Gewicht: 20 kg  
Afmetingen: 500 mm x 1510 mm x 120 mm  
Hot dipped galvanized according to DIN ISO 1461

\* Alle specificaties zijn waarden bij benadering (in sommige gevallen met afrondingen volgens de industriestandaard voor een beter begrip) en zijn uitsluitend bedoeld om het product te begrijpen, maar niet als basis voor de constructie van accessoires, opbergrekken, aanpassingen, combinatieproducten of soortgelijke producten. Wij aanvaarden geen aansprakelijkheid voor eventuele fouten en de daaruit voortvloeiende gevolgen.

\* All data are approximate values (partly with industry-standard rounding for better understanding) and serve only for product understanding, but not as a basis for the design of accessories, storage solutions, adaptations, combination products or the like. All information is without guarantee, for possible errors and resulting consequences we assume no responsibility.

## Item description

Scooter - serial parking

Scooter - serial parking

To park scooters or e-scooters neatly and safely.

- with lockable rings for padlock
- the lockable rings can be opened and closed as required, and a padlock can be connected through the parallel holes on the two plates to secure the appliance
- square tube cross bar 40 x 40 mm
- total width: 1500 mm
- for 5 places
- height: approx. 650 mm above ground
- hot-dip galvanized

- To be fixed by plugs

## Technical specifications

Weight: 20 kg  
Dimensions: 500 mm x 1510 mm x 120 mm  
Hot dipped galvanized according to DIN ISO 1461